

Cub Cadet APPROVED ALLIED EQUIPMENT



SCHWARTZ LOADERS

1050 QT Standard Features:

Tapered boom arms and side frames. Side frames, upright posts and boom are constructed of 10 ga. steel. Box section arms. Swing-away front bumper. Reinforced bucket stops. Double acting cylinders with V-pack seals on rod and O-ring backed urethane seals on the piston. 1-inch chrome plated cylinder rods. Plated steel oil lines. Plated hardware. Integral oil reserve for external hydraulic systems. Bucket level indicator. 3/4-inch diameter anti-rotation pins and grease fittings at main pivot points.

Maximum lift height	67½-inches
Clearance when dumped	51-inches
Reach at maximum height	16-inches
Maximum dump angle	43-degrees
Reach when on the ground	43½-inches
Rollback angle	16-inches
Digging depth	3-inches
Overall height	39½-inches
Lift capacity	350 pounds
Breakout force	675 pounds
Raising time	5.5 seconds
Lowering time	4.0 seconds
Hydraulic system	
Flow	3.5 G.P.M.
Pressure	800 P.S.I.

Attachments

Buckets	38-inch or 48-inch material
Rear weight brackets for tractors with or without 3 pt. hitch (use standard suitcase weights)	

Ordering Codes

Basic Loader is partially assembled and packed with mounting kit, valve, pump and hardware in crate suitable for forklift handling and stacking. Order complete Loader, a bucket and ballast box brackets (if tractor not equipped).

For Cub Cadet models 482 to 882 and 1210 to 1712—requires 500 pounds of ballast	Order complete Loader	#9-2990	at	354 lbs.
	It consists of:			
	Basic Loader	#2-4885		224 lbs.
	Valve, Pump & Hardware	#2-4886		33 lbs.
	Mounting Kit	#2-4887		97 lbs.
For Cub Cadet models 982, 984, 986, 1912 and 1914—requires 400 pounds of ballast	Order complete Loader	#9-2991		364 lbs.
	It consists of:			
	Basic Loader	#2-4885		224 lbs.
	Valve, Pump & Hardware	#2-4886		33 lbs.
	Mounting Kit	#2-4888		107 lbs.

Attachments

Buckets:				
38" material bucket	#2-4889	at		119
48" material bucket	#2-4890			131
Rear Ballast Weight Brackets*				
Cat. 0 3 pt. hitch mounted	#2-4891			14
Bolt-on style for tractors without 3 pt. hitch	#2-4892			21

* Tractor models 482 - 782 require 500 pounds ballast

Model 982 requires 400 pounds ballast.

Specifications subject to change without notice.

For more information call: **Schwartz Products**
129 Pine Street South
Lester Prairie, MN
612-395-2541